

# PLASPERTEX PAINT CO LTD

## Technical Product Data sheet

01.12

Product Name	Floorex semi-gloss
Product reference	PP30
Product description	Single pack solvent borne acrylic floor paint for domestic and light industrial applications. Resistant to moderate alkali, acids and oils. Slip resistant grade contains a polymer aggregate to improve surface grip.
Uses	Decorative and protective floor coating
Pack sizes availability	5 litres
Colour range	Grey, green and red
Specific gravity	Approx 1.2
Flash point	Flammable Flash point approx 40deg C
Recommended Spreading rate	Approx. 6 m <sup>2</sup> /litre per coat (two coats recommended)
Solids content	Approx 48% w/w Approx 32% v/v
Drying time	Approx 4 hours 20°C 65%RH
Over-coating time	Approx 12 hours 20°C 65%RH. Allow min. 24 hours before traffic.
Minimum application temperature	Tolerant of application at low temperatures. Do not apply to surfaces which are damp or at freezing or below
Recommended dry film thickness	Approximately 100 microns
Method of application	Brush or roller
Preparation	Surfaces must be clean, sound and dry and prepared in accordance with BS6150 Painting of buildings – code of practice. Remove any unsound previous coating and weak material and repair with suitable repair products before coating It is recommended that power floated concrete be etched or abraded/grit blasted before coating.
Storage life	Min 12 months in original sealed containers. Protect from frost and direct heat
Thinning/cleaning	The product is supplied ready for use. Wash equipment immediately after use with xylene or white spirit.
Safety precautions	Refer to the safety data sheet before use
Volatile organic content (voc)	Limit for this product Cat A/i 500g/l (2010). This product contains maximum 500g/l VOC
Disposal	When this coating, in its liquid state, as supplied or skinned, becomes a waste, it is categorised as hazardous waste, with code 08 01 11 (list of hazardous wastes) Used containers, drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 04 (list of wastes)  If mixed with other wastes the above waste codes may not be applicable

