

# PLASPERTEX PAINT CO LTD

## Technical Product Data sheet

01.12

Product Name	PVA multi purpose bonding agent and adhesive
Product reference	-
Product description	Polyvinyl alcohol stabilised vinyl acetate homo-polymer dispersion
Uses	General purpose bonding agent, concrete and cement additive and general purpose adhesive. Meets the requirements of BS5270 (PVAC emulsion bonding agents for internal use with gypsum plaster)
Pack sizes availability	5, 10 litres
Colour range	n/a
Specific gravity	Approx 1.07
Flash point	Non flammable
Recommended Spreading rate	n/a
Solids content	Approx 40% w/w
Drying time	n/a
Over-coating time	n/a
Minimum application temperature	Air and surface temperature should be 5°C and rising. Do not apply during damp or frosty weather or when rain is imminent
Recommended dry film thickness	n/a
Method of application	n/a
Preparation	n/a
Storage life	Min 12 months in original sealed containers. Protect from frost and direct heat
Thinning/cleaning	Thin where necessary with clean water. Wash equipment immediately after use with water and detergent
Safety precautions	Refer to the safety data sheet before use
Volatile organic content (voc)	n/a
Disposal	As supplied or containing liquid product – non hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11 Used containers drained/rigorously scraped out and containing only dry residues: categorised as non-hazardous with waste code 15 01 02 (plastic package)

